

Window Type	Series	Test		Report Number	Structural Class	Air Infiltration	Water * Test (PSF)	Min			Max				
		size	bs/vs					Width	Height	bs/vs	Width	Height	bs/vs		
Horizontal Slider	9100	6050	C	310-1671	LC-PG40	0.19	7.5	33	20.5	-	6	0	5	0	36
Double Vent		10050	36	310-1882	R-PG20	0.24	3	49.5	20.5	-	10	0	5	0	36
Double Hung	9200	4080	C	310-1734	LC-PG45	0.11	6.75	17.5	29.5	-	4	0	8	0	C
		3056	C	310-1733	LC-PG45	0.21	6.75	17.5	29.5	-	3	0	5	6	C
		net 52 x 75	C	310-3121	LC-PG35	0.2	5.25	17.5	29.5	-	4	4	6	3	C
Picture Window	9300	6060	-	310-1642	CW-PG50-FW	0.01	7.5	11.5	11.5	-	6	0	6	0	-
Double Hung Fixed	9310	6060	-	310-1670	CW-PG40	0.04	7.5	17.5	20.5	-	6	0	6	0	-
		net 96 x 72	-	310-3312	CW-PG30	0.03	7.5	17.5	20.5	-	8	0	6	0	-
Awning/Casement Fixed	9340 9350	6060	-	310-1644	CW-PG60-FW	0.04	9	17.5	17.5	-	6	0	6	0	-
		8060	-	310-2228	CW-PG50	0.02	9	17.5	17.5	-	8	0	6	0	-
Awning	9400	5030	-	310-1301	AP-C-40	0.02	12	21.5	19.5	-	5	0	3	0	-
		5050	-	310-3266	R-PG-20	0.04	12	21.5	19.5	-	5	0	5	0	-
Radius Casement	9505	3050		F5481.01-901-47	C-CW-PG-75	0.03	12	17.5	23.5		3	0	5	0	-
		3050 Temp glass		F5915.01-907-44	C-CW-PG-95	0.03	15	17.5	23.5		3	0	5	0	-
		3070		F9097.01-901-47	C-CW-PG-60	0.13	12	17.5	23.5		3	0	7	0	-
Radius Picture window	9345	8060		F7067.01-901-47	FW-CW-PG-60	0.02	9	17.5	17.5	-	8	0	6	0	-
Casement	9500	net 35.5 x 60	-	310-1300	CW-PG60	0.03	9	17.5	23.5	-	3	0	5	0	-
		3070	-	310-3271	CW-PG40	0.05	12	17.5	23.5	-	3	0	7	0	-
Radius Picture Window	9700	6060	-	310-1641	CW-PG50-FW	0.01	7.5	Std	Std	-	6	0	6	0	-
		8060	-	310-3402	CW-PG45	0.01	9	Std	Std	-	8	0	6	0	-
Sliding Glass Door XO/OX	9626	8080	C	310-4770	LC-40-SD	0.28	6	30.5	79.5		4	0	8	0	-
Sliding Glass Door OXO		145.5 x 95.5 net	48	310-4770	LC-40-SD	0.28	6	30.5	79.5		8	0	8	0	48
Sliding Glass Door OXO	9626	145.5 x 81.5 Net	48	310-4777	LC-40-SD	0.16	6	30.5	79.5		10	0	6	10	48
Sliding Glass Door OXXO		188.5 x 95.5 Net	48	310-4832	LC-30- SD	0.18	6	30.5	79.5		12	0	8	0	48
Sliding Glass Door OXXO		188.5 x 81.5 Net	48	310-4843	LC-30- SD			30.5	79.5		16	8	8	0	48
Fixed Sash Trans	9628	6060		310-4773	CW-50-FW	0.01	12	Std	Std	-	6	0	6	0	-
Direct set Trans	9630	6060		310-4772	CW-45-FW	0.01	6.89	Std	Std	-	6	0	6	0	-
Inswing	9642	71.5 x 95.5 Net	34	310-4918	LC-35-SHD	0.06	6.06	34	79.5	-	6	0	8	0	34
Inswing with Sidelites		119.5 x 95.5 Net	34	310-5996	LC-35-SHD	0.04	5.43	34	79.5	-	10	0	8	0	34
Outswing	9645	71.5 x 95.50 Net	34	F4031.01-901-47	LC-45-SHD	0.1	6.9	34	79.5	-	6	0	8	0	34
Outswing with Sidelites		119.5 x 95.5 Net	34	310-6020	LC-35-SHD	0.05	5.43	34	79.5	-	6	0	8	0	34

* The water test pressures are done in a controlled environment and performance in the field may vary. Therefore, AAMA requirements should be reduced to 2/3's of the test pressure for field testing.